


## LVC MOS VCXO

## VXSG-06H Series

### ◆特長・用途/Feature

- SMD Package
- Supply Voltage +3.3V
- Output Level LVC MOS
- Frequency range 15MHz ~ 120MHz






### ◆仕様/Specifications

RoHS Compliant

項目 / item	Min	Max	単位 / unit	Note
出力周波数 Frequency range	15	120	MHz	--
動作温度範囲 Operating Temp. range	0	+70	°C	--
電源電圧 Power Supply voltage	+3.3		V	--
消費電流 Current	--	25	mA	--
周波数安定度 Freq. Overall tolerance	±40		10 <sup>-6</sup>	Inclusive of initial tolerance , operating temperature , supply voltage change and Load change.
周波数可変範囲 Freq. control range	±100	--	10 <sup>-6</sup>	Control Voltage (VC) : +0.15V~+3.15V Input impedance : 56kΩ min.
出力レベル Output level	VOH	80%VDD	--	V
	VOL	--	20%VDD	V
Rise time , Fall time	--	5	ns	15 ~ 25MHz
	--	3	ns	25.1 ~ 70MHz
	--	2	ns	70.1 ~ 120MHz
Duty Cycle	40	60	%	50%VDD

### ◆外形寸法/Dimensions unit : mm



Terminal Connections	
Terminal#	Connection
1	Vc or NC
2	NC
3	GND
4	Output
5	NC
6	Vcc or VDD

Pin#1 is NC for SPXG/TCXO